

# DS 102 W

## *The dust and splashproof evolution*

- *for extreme damp surroundings*
- *very dusty surroundings*
- *very hot surroundings*

DS 102 W  
HL



### **Description:**

- The DS 102 W HL ist suitable for darkness and all bad illuminated areas, by the backlighting of the button symbols which are dimmable and the automatic power down by daylight (day/night-design) and is therefor the optimal solution for all narrow surroundings.
- Simplistic design merged with functionality makes this keyboard to a kit of the top class.
- Well proven for use in harsh industrial environments by the full dust and splash proofing combined with extreme scratch resistance.
- About the small space requirement due the compact design is this keyboard also ideally suited for 19" rack mounted drawer unites.

### **Features:**

- Complete protection of the electronic components, all contacts and mechanic guide elements against dust and water splashes (protection IP65).
- Designed for industrial use even under some of the most hostile environments.
- Also suitable for darkness and all bad illuminated areas, by the additional backlighting of the switch symbols
- Ergonomically designed compact shape.
- Convenient and positive operation due to the 3.25 mm travel keys with tactile feel.
- Ergonomically designed keyboard with 102 keys.
- Buttons and case in soft-touch painting.
- Total new circuit-board technologie equipped with our new switch S8.
- LED-indicators for display of standardize operation modes.

### **Order number for example:**

notation: DS 102 W FI USB BL HL5  
article number: .105353010150000HL5

ADPZ

6 rue de la Liberté  
ZI Combeplaine  
42800 Rive de Gier

Tel : (33) 4 77 83 77 03

Fax : (33) 4 77 83 77 16

Web site : [www.adpz.fr](http://www.adpz.fr)

### Mechanical Data:

- Travel 3,25 mm, tactile feel
- Operation force 0,65 N
- 102 buttons, compact layout
- Total height 30 mm at row there
- Durability > 10 million ops.
- Storage temperature -40°C - +70°C
- Operation temperature 0°C - +60°C (optinal -20°C - +60°C)
- Protection IP65

### Layouts:

- All country variants are possible.

### Variants:


- Custom-designed variants are possible. (see our web-site)

### Connecting-Variants:

- PS/2, USB
- Cable straight or spiral-shaped
- Cable length 1,5 m
- Other length are possible

### Detail Views:

- Ergonomic key arrangement for relaxed work.



### Electrical Data:

- Power3 supply + 5 V/DC, 440 mA
- Bidirectional serial output in IBM format
- 2-key-roll-over
- Autorepeat
- CE-conformable
- EMC-conformable
- RoHS-conformable

### Principle:


- Contact by a silicon switch pad with carbon contacts.

### Use Possibilities:

- Extreme damp (even splash water) surroundings
  - Very dusty surroundings
  - Very hot surroundings
  - Bad illuminated areas
  - Extreme industrial surroundings
  - Vehicle installations
  - Aeronautics
  - Navigation Systems
  - and any more
- 
- Very compact, flat style
  - Pull up the cable is almost impossible about the PG7 cable gland



### Dimensions:



L = 405,00mm  
 B = 185,00mm  
 H = 40,40mm  
 H1 = 42,20mm

More information about the measurements can be downloaded from our web-site.

DS 102 W  
HL

ADPZ

6 rue de la Liberté  
 ZI Combeplaine  
 42800 Rive de Gier

Tel : (33) 4 77 83 77 03  
 Fax : (33) 4 77 83 77 16

Web site : [www.adpz.fr](http://www.adpz.fr)