

DS 86 W

The compact keyboard

- for measurements
- machine constructions
- and many more

DS 86 W
HL



Description:

- The DS 86 W HL is the optimal solution for all narrow surroundings.
- External pointing devices like mouse or track ball are no longer necessary, because the keyboard unites all functions.
- Suitable for darkness and all bad illuminated areas, by the backlighting of the switch symbols which are dimmable .
- To build in or for the extern work with small machines or devices in the vehicle installations the navigation systems or aeronautics.
- The compact design and the very low outside measurements predestine this keyboard for many areas.

Features:

- All electronic components and mechanical guides are protected against ingress of dust and water spray (protection IP 65).
- The 1,5 mm key travel and tactile feel ensures positive key operation.
- Ergonomically designed compact shape.
- High quality laser marked key top legends.
- Backlight with LED technology.
- LED-indicators for display of standardize operation mode.
- Integrated mouse function.
- Predestined for the work at machine- and device construction, vehicle installations, aeronautics and navigation systems.

Order number for example:

notation: DS 86 W G USB MR BL HL5LED
article number: 98001023110150000HD5

ADPZ

6 rue de la Liberté
ZI Combeplaine
42800 Rive de Gier

Tel : (33) 4 77 83 77 03
Fax : (33) 4 77 83 77 16

Web site : www.adpz.fr

Mechanical Data:

- Travel 1,5 mm, tactile feel
- Operation force 0,60 N
- 86 buttons, compact layout
- Durability > 1 million ops.
- Storage temperature -40C° - +80C°
- Operation temperature -10C° - +60C°
- Protection IP65

Layouts:

- All country variants are possible.

Variants:

- Custom-designed variants are possible. (see our web-site)

Connecting-Variants:

- DIN, PS/2, USB
- Cable straight or spiral-shaped
- Cable length 1,5 m
- Other length are possible

Detail views:

- Ergonomic, compact illuminated button arrangement on the smallest area.



Electrical Data:

- Power supply + 5 V, 400mA max.
- 3 LED status reading
- CE-conformable
- EMC-conformable
- RoHS-conformable

Principle:

- Bonding by a shifting gear mat on a carbon contact on the SMD-assembled PCB.


Use Possibilities:

- Extreme damp (even splash water) surroundings
- Very dusty surroundings
- Measurement systems
- Machine- and device construction
- Vehicle installations
- Aeronautics
- Navigation Systems
- and any more

- Dimmable about the dimm- and the up or down button
- Integrated fingermouse
- Very compact, flat style



Dimensions:



L = 298,00mm
B = 141,81mm
H = 21,90mm

More information about the measurements can be downloaded from our web-site.



CLAVIERS - PANELS PC - BOÎTIERS

DS 86 W
HL

ADPZ

6 rue de la Liberté
ZI Combeplaine
42800 Rive de Gier

Tel : (33) 4 77 83 77 03
Fax : (33) 4 77 83 77 16

Web site : www.adpz.fr