

## SpillSeal® SAC2 - Washable SmartCard Reader



The SAC2 Smartcard Reader uses the latest smartcard reader / writer technology. It connects to your computer via a USB port, and is therefore fully compatible with Windows 98, ME, 2000, XP and Vista.

The SmartCard Reader is compliant with all common smartcard standards, and is supported by the PC/SC Windows driver.

The SAC2 Smartcard Reader is a CCID & EMV certified Plug & Play reader for PCs with USB 2.0 interface. Beside its easy installation, it reads memory and microprocessor cards.



The SAC2 is designed to meet all major standards like ISO 7816, EMV 2000, Microsoft WHQL, USB CCID, PC/SC, HBCI (Home Banking Computer Interface), the PC-2001 specification and many more.

The usage within an application is based on standardised interfaces like PC/SC, OCF (Open Card Framework) or CT-API. The USB CCID support makes the integration in an existing system the easiest ever by connecting host and Smartcard Reader without the need of additional drivers.

SAC2 Smartcard Reader fulfils the Security and Hygiene demands of many applications: Healthcare, Government, Education, Financial.

**Washable and Waterproof to IP66 and NEMA4X**  
Sealed keys lets you wash and fully clean the keyboard.

### Antibacterial Protection

Is incorporated in the plastic providing a powerful broad-spectrum inorganic, silver-based biocide for antibacterial protection.

### Easy to Disinfect

Immerse in antibacterial solutions to reduce the spread of germs.

### Smartcard Reader Drivers

## SAC2/SRC5/SRC6 Smartcard Reader Drivers

Smartcard Reader SC2.0 Drivers	Win 98	Win ME	Win NT	Win 2000	Win XP	Win Vista	Win CE	Linux	Mac OS X
<a href="#">SAC2/SRC5/SRC6 Smartcard Reader - 98, ME, 2000 and XP</a>	Y	Y	Y	Y	Y	-	-	-	-
<a href="#">SAC2/SRC5/SRC6 Smartcard Reader - 98, ME, 2000, XP and VISTA</a>	Y	Y	Y	Y	32/64	32/64	-	-	-
<a href="#">SAC2/SRC5/SRC6 Smartcard Reader - Windows CE</a>	-	-	-	-	-	-	Y	-	-
<a href="#">SAC2/SRC5/SRC6 Smartcard Reader - Linux</a>	-	-	-	-	-	-	-	Y	-
<a href="#">SAC2/SRC5/SRC6 Smartcard Reader - Mac OS X</a>	-	-	-	-	-	-	-	-	Y

Note: 32/64 provide drivers for both 32bit and 64bit Operating Systems.

### Package Content

- SpillSeal® Protected SAC2 SmartCard Reader
- Installation / User Guide

### System Requirements

- IBM® PC or compatible
  - USB Only
- Windows® 98/ME/2000/XP/Vista/CE/Linux

Specifications	
Water and Dust Resistance	IP66 / NEMA4X
Antibacterial Protection	Silver-based Antibacterial Additive
OS Compatibility	Windows 98/ME/2000/XP/Vista/CE/Linux
Connection Type	USB 1.1
Cable Length	2M
Card Contacting Unit	100,000 insertion cycles
Card Power Supply	60mA
Status Indicator	Duo-LED
Transmission Speed with PC	12Mbps
Protocols	T=0, T=1, 2-wire: SLE 4432, SLE 4442 (S=10), 3-wire: SLE 4418, SLE 4428 (S=9), I2C (S=8), SLE 4404
SmartCards Supports	5V, 3V and 1.8V SmartCards
Drivers	PC/SC, CT-API
Certifications	PC/SC, EMV 2000, FCC, CE, RoHS, WEEE

Unit Dimensions	
Length (mm)	78
Width (mm)	45
Height (mm)	60
Weight	72gms
Unit Pack	
Width (mm)	105
Depth (mm)	50
Height (mm)	110
Unit Pack Weight	130gms
Outer Carton	
Outer Carton Quantity	10
Width (mm)	510
Depth (mm)	123
Height (mm)	110
Outer Carton Weight	1.4KG

ADPZ

6 Rue de la Liberté - ZI de Combeplaine

Tel : (33) 4 77 83 77 03 - Fax : (33) 4 77 83 77 16

Web site : [www.adpz.fr](http://www.adpz.fr)